## Local structure and performance of bulk-heterojunction polymer solar cells measured by light-modulated scanning tunneling spectroscopy.

T. Ochiai<sup>1,2</sup>, T. Yasuda<sup>3</sup>, H. Kato<sup>1</sup> Y. Kobayashi<sup>1</sup> N. Takeuchi<sup>1</sup>, S. Yoshida<sup>1</sup>, O. Takeuchi<sup>1</sup>, H. Shigekawa<sup>1</sup> Institute of Applied Physics, University of Tsukuba, Japan, <sup>2</sup>Takano Co., Ltd., Japan, <sup>3</sup>NIMS, Japan

To realize highly power-conversion efficient polymer solar cells, many researchers study solar cells with Bulk-Heterojunction (BHJ) structure. In order to proceed such studies, characterization of BHJ cells on nanoscale is necessary. In this study, we applied "Light-Modulated Scanning Tunneling Spectroscopy (LM-STS)" to BHJ polymer solar cells, and observed the local structure and performance on polymer solar cells. As samples, we prepared for two BHJ solar cells. One is made of MDMO-PPV:PCBM mixture, the other is P3HT:PCBM mixture. Figure 1. shows that result of LM-STS on the former. Figure 1 (a) is topographic image, (b) short circuit current (*Isc*) mapping, (c) is open circuit voltage (*Voc*) mapping. It can be seen that *Isc* and *Voc* varies with ~100 nm

scales. On the presentation, we also present the result on the P3HT:PCBM mixture and discuss the difference in the spatial distribution of the performance in terms of the differences in the compositions and structures of the cells.





